



LAYFLAT HOSE



July 2008

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





LAYFLAT HOSE INDEX

Description	Page
Sunny Blue - Low Pressure	51
Sunny Brick Red - Heavy Duty	51
Blue - High Pressure	51
Fire Hose - Percolating Canvas & PU	52
Fire Hose - Rubber	53
Irrigation Drag Hose	54
Oroflex 10 Air/Water	55
Oroflex 20 Air/Water - High Pressure	55
Dewatering PU	56
Petroline	56
Potable Water	56

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





PVC LAYFLAT

SUNNY BLUE PVC - LOW PRESSURE

The Sunny Blue low pressure layflat has a one layer construction which means it can be pierced without causing delamination. Suitable for Trickle Irrigation applications, it is also suitable for light duty dewatering applications.

ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	MPa	psi		
38	0.51 MPa	75 psi	100	L-LSB-038-100
51	0.45 MPa	65 psi	100	L-LSB-050-100
63	0.40 MPa	60 psi	100	L-LSB-063-100
76	0.35 MPa	50 psi	100	L-LSB-075-100
102	0.30 MPa	45 psi	100	L-LSB-100-100
152	0.30 MPa	45 psi	100	L-LSB-150-100
203	0.30 MPa	45 psi	100	L-LSB-200-100
250	0.25 MPa	36 psi	100	L-LSB-250-100

SUNNY BRICK RED PVC - HEAVY DUTY

Excellent abrasive resistance allowing it to be used in heavy duty dewatering application, where water may be mixed with solid particles. Also used on small irrigators.

ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	MPa	psi		
38	1.03 MPa	152 psi	67 100	L-LSR-038-100
51	1.03 MPa	152 psi	100	L-LSR-050-100
63	1.03 MPa	152 psi	100	L-LSR-063-100
76	0.9 MPa	130 psi	100	L-LSR-075-100
102	0.9 MPa	130 psi	100	L-LSR-100-100
152	0.68 MPa	102 psi	100	L-LSR-150-100
203	0.50 MPa	75 psi	100	L-LSR-200-100

ROYAL BLUE PVC - HIGH PRESSURE

Blue covered, two piece layflat with a black tube.

ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	MPa	psi		
19	1.0 MPa	140 psi	50	L-LHB-020-050
25	1.0 MPa	140 psi	50 100	L-LHB-025-***
32	0.9 MPa	130 psi	100	L-LHB-032-100
38	0.8 MPa	115 psi	100	L-LHB-038-100
51	0.8 MPa	115 psi	100	L-LHB-050-100

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



FIRE HOSE LAYFLAT

SABRE—PERCOLATING CANVAS FIRE HOSE (Forestry use)



ID (MM)	PRESSURE		COIL LENGTHS (METRES)	PART NO
	PROOF	BURST		
25	2100 Kpa	5200 Kpa	30	L-SAB-025-030
38	2100 Kpa	5200 Kpa	30	L-SAB-038-030
50	2100 Kpa	5200 Kpa	30	L-SAB-050-030
64	2100 Kpa	5200 Kpa	30	L-SAB-063-030

EXCALIBUR—`Canvas Type' Fire Hose Rubber Inner Lining

Non Percolating. Manufactured to AS2792-1992 Class L, M and H.



ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	kPa	psi		
25	1400 kPa	203 psi	30	L-EFH-025-***
38	1400 kPa	203 psi	30	L-EFH-038-***
50	1400 kPa	203 psi	30	L-EFH-050-***
64	1400 kPa	203 psi	30	L-EFH-063-***
76	1400 kPa	203 psi	30	L-EFH-075-***
90	1000 kPa	145 psi	30	L-EFH-090-***
102	1000 kPa	145 psi	30	L-EFH-102-***

CAVALIER—Fire Hose with Red PU Coating for Abrasion resistance



Lightweight super strength hose suitable for industrial and commercial fire protection, general usage in industry, mining, engineering and fire services.

ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	kPa	psi		
25	2100 kPa	300 psi	30	L-CFH-025-***
38	2100 Kpa	300 psi	30	L-CFH-038-***
50	2100 Kpa	300 psi	30	L-CFH-050-***
64	2100 kPa	300 psi	30	L-CFH-063-***
75	2100 Kpa	300 psi	30	L-CFH-075-***
90	2100 Kpa	300 psi	30	L-CFH-090-***
102	2100 Kpa	300 psi	30	L-CFH-102-***

All dimensions are nominal.

Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



CENTURION FIRE HOSE

Centurion is rot proof eliminating the need for drying after use. Manufactured to AS2792-1992 and meets the approval of the Australian Army DEF 5195A 1992.



ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	kPa	psi		
25	1500 kPa	220 psi	30	L-CEH-025-***
38	1500 kPa	220 psi	30	L-CEH-038-***
50	1500 kPa	220 psi	30	L-CEH-050-***
64	1500 kPa	220 psi	30	L-CEH-063-***
76	1500 kPa	220 psi	30	L-CEH-075-***
90	1500 kPa	220 psi	30	L-CEH-090-***
102	1500 kPa	220 psi	30	L-CEH-102-***

RAPIER HEAVY DUTY FIRE HOSE—RUBBER

Heavy Duty PVC Nitrile rubber covered fire hose ideally suited for brigades and industries where hoses require protective covers against abrasion damage and chemical degradation.



ID (MM)	WORKING PRESSURE		COIL LENGTHS (METRES)	PART NO
	kPa	psi		
25	1500 kPa	220 psi	30 100	L-RFH-025-***
38	1500 kPa	220 psi	30 100	L-RFH-038-***
50	1500 kPa	220 psi	30 100	L-RFH-050-***
64	1500 kPa	220 psi	30 100	L-RFH-063-***
76	1500 kPa	220 psi	30 100	L-RFH-075-***
90	1500 kPa	220 psi	30 100	L-RFH-090-***
102	1500 kPa	220 psi	30 100	L-RFH-102-***

ARMTEX 10 RUBBER FIRE HOSE

Seamless Extruded Rubber Layflat for the professional firefighter.
Meets Australian Standards for Rubber Fire hose AS2792-1992 Class M&H
10yr Pro Rata warranty when used in normal conditions Temperature: -50degC- +60deg C



ID (MM)	OD (MM)	BURST PRESSURE	TEST PRESSURE	COIL LENGTHS (METRES)	PART NO
38	43	900 psi	600psi	30	G-ARM-038-***
64	70	750psi	500psi	30	G-ARM-064-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



RUBBER LAYFLAT



BANDAMA 2000 IRRIGATION DRAG HOSE

Hard wearing Traveling Irrigator Hose with a 10 year Pro rata warranty.

The integrated tube and cover offers excellent abrasion resistance, minimal friction losses and UV resistance.

Black Nitrile tube and cover, High strength circular woven textile braid, temp range -30 to +70 C

Longer Lengths available on request.

ID (MM)	OD (MM)	W.P. (MPA)	BEND RADIUS (MM)	COIL LENGTHS (METRES)	PART NUMBER
65	73.2	1.0	1200	100 / 150 / 200	G-FTX-065-***
75	83.2	1.0	1400	100 / 150 / 200	G-FTX-075-***
90	98.2	1.0	1500	100 / 150 / 200	G-FTX-090-***
105	113.2	1.0	1500	100 / 150 / 200	G-FTX-100-***
114	122.2	1.0	1500	100 / 150 / 200	G-FTX-115-***
125	133.2	1.0	1700	100 / 150 / 200	G-FTX-125-***
150	158.2	1.0	1900	100 / 150 / 200	G-FTX-150-***



All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





OROFLEX 10 AIR / WATER DELIVERY

General Purpose rubber layflat hose for air and water delivery. The unique construction and design offers high abrasion resistance, UV stabilization, and minimal friction losses.

Black Nitrile tube and cover, High strength circular woven textile braid, temp range -30 to +70 C



ID (MM)	OD (MM)	W.P. (MPA)	BEND RADIUS (MM)	COIL LENGTHS (METRES)	PART NO
38	42	1.0	700	100	G-STX-038-***
50	54	1.0	1100	100	G-STX-050-***
75	80	1.0	1450	100	G-STX-075-***
100	105	1.0	1700	100	G-STX-100-***
150	156	1.0	2250	100	G-STX-150-***
200	206	1.0	3000	100	G-STX-200-***
250	257	1.0	3300	100	G-STX-250-***

OROFLEX 20 AIR / WATER H/PRESSURE (YELLOW)

As per Oroflex 10, with high pressure rating for the most demanding applications.

Black Nitrile tube and cover, High strength circular woven textile braid, temp range -30 to +70 C



ID (MM)	OD (MM)	W.P. (MPA)	BEND RADIUS (MM)	COIL LENGTHS (METRES)	PART NO
19	24	2.0	250	60	G-ORF20-020-***
25	32	2.0	250	60	G-ORF20-025-***
38	45	1.4	650	60	G-ORF20-038-***
52	59	1.7	1200	60	G-ORF20-050-***
75	83	1.7	1300	60	G-ORF20-075-***
100	108	1.7	1700	60	G-ORF20-100-***
150	158	1.7	2000	60	G-ORF20-150-***
200	208	1.7	4000	60	G-ORF20-200-***

WE OFFER FITTED ASSEMBLIES WITH BAUERS / CAMLOCKS / FLANGES ETC ON THE ABOVE HOSES.
PLEASE CALL FOR QUOTATION

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



ULTRAMAN PU

Extruded PU. Hardwearing suitable for mine dewatering applications. Green Polyurethane throughout.
Temperature: -50degC- +75deg C



ID (MM)	OD (MM)	W.P. (MPA)	BEND RADIUS (MM)	COIL LENGTHS (METRES)	PART NO
152	160	1.6	1700	100	G-ULT-150-***
200	208	1.0	3000	100	G-ULT-200-***

PETROLINE—ANTISTATIC

Extruded PU hose, chemical and abrasion resistant. Suitable for use with Fuels & Chemicals, refuelling truck, rail and ship to shore.
Applications in fuel terminals & depots. Built in Copper anti-static wire. -55deg C—+65Dec C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT PER MTR (KG)	COIL LENGTHS (METRES)	PART NO
40	42	0.95	0.40	100 / 200	G-ANT-038-***
50	54	1.85	0.55	100 / 200	G-ANT-050-***
64	68	1.02	0.75	100 / 200	G-ANT-063-***
76	80	1.45	0.95	100 / 200	G-ANT-075-***
102	106	1.25	1.40	100 / 200	G-ANT-100-***
152	156.5	1.1	2.50	100 / 200	G-ANT-150-***

FLEXIBORE—POTABLE WATER

Flexibore is a flexible riser used for ground water pumping. Typical applications are mine de-watering, domestic and municipal water supply, test pumping, rural and industrial bore water retrieval.
Max temp 45degC
Approved for use with Potable water AS4020.



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT PER MTR (KG)	COIL LENGTHS (METRES)	PART NO
40	42	1.5	0.27	Up to 200mtr	G-PWH-038
51	54	3.0	0.56	Up to 200mtr	G-PWH-050
76	80	2.2	0.91	Up to 200mtr	G-PWH-075
102	106	2.0	1.24	Up to 200mtr	G-PWH-100
127	132	2.0	1.76	Up to 200mtr	G-PWH-125
152	157	2.0	1.96	Up to 200mtr	G-PWH-152

WE ALSO SUPPLY THE CABLES & STAINLESS STEEL FITTINGS FOR FLEXIBORE. PLEASE CALL FOR MORE INFORMATION

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





FLUID HANDLING SOLUTIONS

Abrasives
Airbrake Fittings
Airline Couplings
Automotive Belts
Ball Valves
Bauer Fittings
Band-It
Brass Fittings
Camlock Fittings
Chain & Sprockets
Check Valves
Claw Couplers
Composite Hose
Couplings
Ducting
Filter Regulators
Fire Fittings
Gate Valves
Glue
Hose Assemblies
Hose Fittings
Hose Reels
Hydraulic Adaptors
Hydraulic Couplings
Hydraulic Hose
Industrial Belts
Layflat Hose
Nozzles
Nylon Tube
Pipe Fittings
Pneumatics
Poly Fittings
Polyurethane Tube
Pool Hose
Pressure Gauges
PTFE Fittings
Push-In Fittings
PVC Hose
Quick Couplings
Rubber Hose
Sheet Rubber
Silicone Hose
Stainless Steel Fittings
Stainless Steel Hose
Strainers
Steam Fittings
Super Clamps
Tank Fittings
Tubing
Wormdrives

LOCATIONS

BRAESIDE
Unit 5 / 200-208
Boundary Rd
Braeside VIC. 3195



BAYSWATER
Unit 1 / 477
Dorset Rd
Bayswater VIC. 3153

CUSTOMER SERVICE

P: 1300 349 320

F: 1300 349 321

SYDNEY
25 Clyde St
Rydalmere NSW. 2116



NEWCASTLE
Unit 2 / 34
Portside Crescent
Maryville NSW. 2293

www.fhshose.com.au