



RUBBER HOSE



July 2008

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





RUBBER HOSE

INDEX

Description	Page
Air / Water Delivery Hose	27
Water Suction Hose	28
Moulded Air / Water Hose	29
Car Heater Hose	29
Pressure Washer & Jack Hammer Hose	30
Fras Air Hose	31
Bull Hose	31
Steel Air Hose	32
Hot Air Blower Hose	32
Push Lock Hose	33
Oil Delivery Hose	33
Fuel Line	33
Marine Fuel Hose	34
Oil Suction Hose	34
Petrol Bowser Hose	34
Marine Exhaust Hose	35
Multi-Purpose Oil Resistant Hose	36
Welding Hose	37
Washdown Hose	38
Steam Hose	39
Food / Beverage Hose	39 & 40
Concrete / Sand & Shot Hose	41
Material Handling Hose	42
Cable Trailing FRAS Hose	43
Chemical Hose	44

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





AIR / WATER HOSE

AIR / WATER DELIVERY 1 Mpa Green Stripe



Heavy Duty general purpose water discharge Hose. Black / Green Stripe
Black SBR tube and cover, synthetic ply reinforcement, Black cover . temp range -40 to+85 C

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	23.0	1.00	0.32	20	W-WD1-012-***
20	29.0	1.00	0.43	20	W-WD1-020-***
25	35.0	1.00	0.75	20	W-WD1-025-***
32	42.0	1.00	0.96	20	W-WD1-032-***
38	48.0	1.00	1.12	20	W-WD1-038-***
45	59.0	1.00	1.48	20	W-WD1-045-***
50	61.0	1.00	1.45	20	W-WD1-050-***
57	68.0	1.00	1.65	20	W-WD1-057-***
63	73.0	1.00	1.60	20	W-WD1-063-***
75	87.0	1.00	2.32	20	W-WD1-075-***
100	114.0	1.00	3.36	20	W-WD1-100-***
115	132.0	1.00	4.80	20	W-WD1-115-***
125	142.0	1.00	3.94	20	W-WD1-125-***
150	169.0	1.00	7.07	20	W-WD1-150-***
200	218	0.80	6.19	CUT	W-WD1-200-***
250	271	0.80	8.67	CUT	W-WD1-250-***

AIR / WATER HEAVY DUTY 2 Mpa Blue Stripe



A Heavy Duty Air / Water hose for applications such as quarry, heavy industry and construction.
Black SBR tube and cover, synthetic ply reinforcement, temp range -35 to +88 C

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	23.0	2.00	0.46	20	W-AH2-012-***
20	31.0	2.00	0.64	20	W-AH2-020-***
25	37.0	2.00	0.76	20	W-AH2-025-***
32	46.0	2.00	1.30	20	W-AH2-032-***
38	51.0	2.00	1.19	30.5	W-AH2-038-***
50	63.0	2.00	1.38	30.5	W-AH2-050-***
63	76.0	2.00	1.73	30.5	W-AH2-063-***
75	90.0	2.00	2.34	30.5	W-AH2-075-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



WATER SUCTION / DELIVERY



Heavy Duty Water Suction and Delivery Hose for full suction and high discharge pressures.
Black SBR tube and cover, synthetic ply reinforcement, incorporating Steel Helix, Black with Green Stripe
temp range 40° to +85 °C

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
20	29.0	1.00	0.49	30.5	W-WS4-020-***
25	35.0	1.00	0.80	20	W-WS4-025-***
32	42.0	1.00	0.97	20	W-WS4-032-***
38	49.0	1.00	1.24	20	W-WS4-038-***
45	56.0	1.00	1.55	20	W-WS4-045-***
50	63.0	1.00	1.77	20	W-WS4-050-***
57	72	1.00	2.00	20	W-WS4-057-***
63	75.5	1.00	2.37	20	W-WS4-063-***
76	89.0	1.00	2.78	20	W-WS4-075-***
90	101.0	1.00	3.60	30.5	W-WS4-090-***
100	117.0	1.00	4.26	20	W-WS4-100-***
115	131.0	0.80	6.90	20	W-WS4-115-***
125	145.0	0.80	7.23	20	W-WS4-125-***
150	172.5	0.80	8.40	20	W-WS4-150-***
203	224.0	0.80	17.82	6 / 10	W-WS4-200-***
250	283.0	0.80	24.37	6/ 10	W-WS4-250-***

CORRUGATED WATER SUCTION WITH SOFT ENDS (CUFFS)



Designed for water suction and discharge service where a flexible but durable hose application is needed.
Supplied with cuffed ends for ease of fitting installation.
Black SBR tube and cover (corrugated), synthetic ply reinforcement incorporating Steel Helix, temp range -35°to70° C

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
76	95	0.30	3.52	6	W-WS5-075-006
100	123	0.30	3.70	3/6	W-WS5-100-***
150	176	0.30	7.00	3/6	W-WS5-150-***
200	240	0.30	10.00	3/6	W-WS5-200-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



BLACK GENERAL PURPOSE AIR/WATER

General purpose BLACK air, and water delivery hose that is suitable for many agricultural chemicals
Black EPDM tube and black cover, synthetic ply reinforcement, temp range -40 to +100 C



MM	ID (INCHES)	OD (MM)	W.P. (MPA) (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
5	(3/16)	11.1	1.36 (200)	0.09	228.5 (750)	M-GPB-005-***
6	(1/4)	12.7	1.36 (200)	0.13	228.5 (750)	M-GPB-006-***
8	(5/16)	15.1	1.36 (200)	0.19	213.0 (700)	M-GPB-008-***
10	(3/8)	16.7	1.36 (200)	0.21	198.0 (650)	M-GPB-010-***
12	(1/2)	20.7	1.36 (200)	0.31	152.0 (500)	M-GPB-012-***
16	(5/8)	24.6	1.36 (200)	0.36	137.0 (450)	M-GPB-016-***
20	(3/4)	28.2	1.36 (200)	0.48	106.7 (350)	M-GPB-020-***
25	(1)	35.7	1.36 (200)	0.66	76.2 (250)	M-GPB-025-***

RED GENERAL PURPOSE AIR/WATER

General purpose red air, and water delivery hose that is suitable for many agricultural chemicals.
Black EPDM tube and red cover, synthetic ply reinforcement, temp range -40 to +100 C



MM	ID (INCHES)	OD (MM)	W.P. (MPA) (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
6	(1/4)	12.7	1.36 (200)	0.13	228.5 (750)	M-GPR-006-***
10	(3/8)	16.7	1.36 (200)	0.21	198.0 (650)	M-GPR-010-***
12	(1/2)	21.4	1.70 (250)	0.34	152.0 (500)	M-GPR-012-***
20	(3/4)	28.2	1.36 (200)	0.48	106.7 (350)	M-GPR-020-***
25	(1)	35.7	1.36 (200)	0.66	76.2 (250)	M-GPR-025-***

OTHER COLOURS AVAILABLE ON REQUEST (YELLOW, BLUE, GREEN) maybe subject to min order qty.

CAR HEATER HOSE

Car Heater Hose that is suitable for low pressure water discharge and automotive coolant lines
Black EPDM tube and cover, synthetic ply reinforcement, temp range -40 to +100 C



MM	ID (INCHES)	OD (MM)	W.P. (MPA) (PSI)	WEIGHT (KG / M)	COIL LENGTHS METRES (FEET)	PART NO
12	(1/2)	19.8	0.85 (125)	0.27	152.0 (500)	M-CHH-012-***
16	(5/8)	23.0	0.61 (90)	0.32	152.0 (500)	M-CHH-016-***
20	(3/4)	26.2	0.48 (70)	0.38	137.0 (450)	M-CHH-020-***

****REF TO AUTOMOTIVE PRICE LIST FOR 15MTR BOXES**

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



PRESSURE WASHER HOSE BLUE

Blue non marking, oil resistant hose for use on pressure washer machines up to 3000 psi.
Black Neoprene tube and blue neoprene cover, one wire braid reinforcement, temp range -40 to +120 C



ID (MM)	OD (MM)	W.P. (MPA (PSI))	WEIGHT (KG/M)	COIL LENGTHS (METRES (FEET))	PART NO
6.4	12.7	20.7 (3000)	0.21	152.0 (500)	M-PWH-006-***
9.5	17.5	20.7 (3000)	0.29	152.0 (500)	M-PWH-010-***
12.7	21.4	20.7 (3000)	0.30	152.0 (500)	M-PWH-012-***

****AVAILABLE IN PRE-ASSEMBLED LENGTHS WITH FEMALE BSP FITTINGS, CALL FOR PRICING.**

FIRE ENGINE BOOSTER HOSE RED

For use in high pressure fire engine booster service. Also has many other heavy duty industrial and municipal operations.



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
20	32	5.4	.59	30.5 61	M-FEB-020-***
25	39	5.4	.81	30.5 61	M-FEB-025-***
25	39	FITTED WITH M/F BARWAYS		15.2	M-FEB-025-015A
25	39	FITTED WITH M/F BARWAYS		30.5	M-FEB-025-030A
25	39	FITTED WITH M/F BARWAYS		61	M-FEB-025-061A

YELLOW PNEUMATIC / JACK HAMMER HOSE

Economical air & water hose. It is suitable for industrial, construction and agricultural applications.
Black SBR tube and yellow cover, synthetic ply reinforcement, temp range -0 to +70 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	21.0	1.75	0.33	20/100	M-APY-012-***
20	29.0	1.75	0.51	20/60	M-APY-020-***
25	37.0	1.40	0.81	20/60	M-APY-025-***



All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



NEW

FRAS AIR HOSE—COALMASTER

Designed specifically for the conveyance of air and water in coal mining applications. Black SBR tube & Chloroprene cover with synthetic ply reinforcement. -40 - +100degC. Conforms to AS2660 Class B requirements.



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	23	1.75 (254)	0.41	20	W-FAD-012-***
20	29	1.75 (254)	0.55	20	W-FAD-020-***
25	36	1.75 (254)	0.74	20	W-FAD-025-***
32	46	1.75 (254)	1.27	20	W-FAD-032-***
38	52	1.75 (254)	1.46	20	W-FAD-038-***
50	65	1.75 (254)	1.86	20	W-FAD-050-***
63	81	1.75 (254)	2.65	20	W-FAD-063-***
76	93	1.75 (254)	3.15	20	W-FAD-075-***

**Longer lengths available on request

NEW

YELLOW BULL HOSE—FABRIC BRAID

Heavy Duty Air hose designed for use in mining and construction. Yellow with Blue Stripe, Oil mist resistant. Temp range -40 to +85 C



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	35	2.0 (305)	.754	20	W-AH6-025-020
50	65	2.0 (305)	2.112	20	W-AH6-050-020

NON CONDUCTIVE AIR HOSE BLUE

Heavy Duty Blue air hose for rough industrial conditions as well as server mining applications. Non-Conductive >1 mega Ohm per inch @1000volts. Oil Mist resistant.



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
19	31	2.7 (395)	0.67	30.5	W-AH3-020-***
25	38	2.7 (395)	0.86	30.5 61	W-AH3-025-***
32	45	2.7 (395)	1.10	30.5 61	W-AH3-032-***
38	52	2.7 (395)	1.28	30.5 61	W-AH3-038-***
50	65	2.7 (395)	1.65	30.5 61	W-AH3-050-***
63	80	2.7 (395)	2.45	30.5 61	W-AH3-063-***
76	94	2.7 (395)	3.20	30.5 61	W-AH3-075-***

AIR BRAKE HOSE - REF TO AUTOMOTIVE BOOK

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



STEEL AIR (HEAVY DUTY BULL HOSE)

Steel Wire reinforced air hose for severe applications in mining, quarries and construction applications
Black SBR tube and yellow cover, Plies of steel wire, temp range -40° to +100° C.



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	39.5	4.50 (650)	1.10	30.5	W-AH5-025-***
38	56.0	4.50 (650)	2.03	20/ 30.5	W-AH5-038-***
50	68.0	4.10 (595)	2.39	20/ 30.5	W-AH5-050-***
63	82.0	3.20 (465)	3.29	20/ 30.5	W-AH5-063-***
75	98.0	5.10 (740)	4.91	20/ 30.5	W-AH5-075-***

PYROFLEX HOT AIR BLOWER (HARDWALL)

Conveyance of hot air from compressors to tanks on bulk dry carriers
Black Versigard tube and cover (corrugated), synthetic ply reinforcement incorporating Steel Helix, temp range -29 to +163 C



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG / M)	COIL LENGTHS (METRES)	PART NO
75	90	0.80 (116)	2.88	20	W-AHA-075-***
100	117	0.34	3.57	30.5	W-AHA-100-***

HOT AIR BLOWER WITHOUT WIRE HELIX (SOFTWALL)

Applications requiring conveyance of hot air with high temperatures.
Black EPDM tube and cover, synthetic ply reinforcement, temp range -40 to +176 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
75	89.0	0.80	2.40	20/ 60	W-AHS-075-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



AIR / WATER PUSH LOCK



PUSH LOCK JIFFY HOSE MSHA APPROVED

Oil resistant hose for use with air tools to convey water mild chemicals and various petroleum products. Light and flexible Black Nitrile tube and neoprene cover, synthetic ply reinforcement, temp range -40 to +100 C. MSHA approved

ID (MM)	OD (MM)	W.P. (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
6	13	300	0.13	152	W-PLH-006(**)-***
10	16	300	0.18	152	W-PLH-010(**)-***
12	19	300	0.22	152	W-PLH-012(**)-***
16	23	300	0.30	152	W-PLH-016(**)-***
19	26	300	0.39	122	W-PLH-020(**)-***

**Add Colours:
(BK) - Black—standard
(BL) - Blue
(GN) - Green
(RD) - Red
(GY) - Grey

OIL, GAS, FUEL TRANSFER HOSES

OIL DELIVERY

Delivery of a wide range of petroleum products up to a 50% aromatic content. Black Nitrile tube and cover, synthetic ply reinforcement, temp range -15 to +70 C



ID (MM)	OD (MM)	W.P. (MPA)	MASS (KG/M)	COIL LENGTHS (METRES)	PART NO
19	28.0	1.00	0.44	20	W-OD1-020-***
25	35.0	1.00	0.74	20	W-OD1-025-***
32	42.0	1.00	0.91	20 / 60	W-OD1-032-***
38	50.0	1.00	1.30	20	W-OD1-038-***
45	56.0	1.00	1.22	20	W-OD1-045-***
50	65.0	1.00	2.00	20	W-OD1-050-***
60	73.0	1.00	2.04	20	W-OD1-060-***
63	78.0	1.00	2.34	20	W-OD1-063-***
76	92.0	1.00	3.31	20	W-OD1-075-***
100	118.0	1.00	3.90	20	W-OD1-100-***

FUEL LINE / VAPOUR EMISSION HOSE

Fuel Line or vapour emission hose that meets SAE 30R7. The cover resists heat ozone, oil & grease Black Nitrile tube and black Neoprene cover, synthetic ply reinforcement , temp range -34 to +120 C



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
5	10.3	0.50 (75)	0.11	152 **	M-OFL-005-***
6	12.7	0.35 (50)	0.15	152 **	M-OFL-006-***
8	14.3	0.35 (50)	0.17	152 **	M-OFL-008-***
10	15.9	0.35 (50)	0.21	152 **	M-OFL-010-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



MARINE FUEL LINE

(Meets USCG/SAE J1527 Type A1)

Fuel Line for Marine Gasoline Tanks. For fuel feed and vent applications on marine pleasure craft.
Black Nitrile tube and black cover, synthetic ply reinforcement



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
6	16	0.34 (49)	0.25	61	M-OMF-006-***
8	18	0.34 (49)	0.28	61	M-OMF-008-***
10	20	0.34 (49)	0.30	76.2	M-OMF-010-***
12	23	0.25 (36)	0.39	76.2	M-OMF-012-***
16	26	0.25 (36)	0.52	76.2	M-OMF-016-***

OIL SUCTION/DELIVERY

Oil hose for use with hydraulic systems as an oil return hose or various petroleum products.
Black Nitrile tube and cover, synthetic ply reinforcement incorporating Steel Helix. Suitable for petroleum products up to 50% aromatic content temp range -20 to +75 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
19	30.0	1.00	0.68	20	W-OS4-020-***
25	37.0	1.00	0.91	20	W-OS4-025-***
32	43.0	1.00	1.03	20	W-OS4-032-***
38	49.0	1.00	1.20	20	W-OS4-038-***
45	57.0	1.00	1.60	6 / 20	W-OS4-045-***
50	63.0	1.00	1.74	20	W-OS4-050-***
57	70.0	1.00	2.40	6	W-OS4-057-***
63	78.0	1.00	2.75	20	W-OS4-063-***
76	90.0	1.00	4.15	20	W-OS4-075-***
90	105.0	1.00	4.15	20	W-OS4-090-***
102	118.0	1.00	4.77	20	W-OS4-100-***
150	174.0	1.00	10.85	20	W-OS4-150-***

BOWSER / PUMP HOSE

Hard wall hose for fuel dispensing. Suitable for diesel, leaded, unleaded and oxygenated gasoline.
Black Nitrile tube and black hypalon, synthetic ply reinforcement incorporating dual Helix Wire.
Temp range -40 to +82 C



ID MM (INCHES)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
16	26.2	1.0 (150)	0.57	152.0 (500)	M-FBH-016-***
20	29.8	1.0 (150)	0.67	152.0 (500)	M-FBH-020-***
25	36.9	1.0 (150)	0.89	152.0 (500)	M-FBH-025-***
ASSEMBLY C/W 3/4" NPT/BSP MALE ENDS					
16	36.9	1.0 (150)	2.89 ea	5.00 (16)	M-FBH-016-005A

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



MARINE EXHAUST HARDWALL - CORRUGATED COVER

Designed and approved for the delivery of cooling water and exhaust gas in boat engines pleasure craft. Ozone, heat and oil resistant cover. Temp Range - 40°C to +100°C. Black corrugated NR-SBR compound cover with smooth NR-SBR tube. Lloyds Type Approval - 98/00089



ID (MM)	W.P. (PSI)	MAX LENGTH (M)	PART NO
38	145	20	W-OME-038-***
44	145	20	W-OME-044-***
51	145	20	W-OME-050-***
60	145	20	W-OME-060-***
63	145	20	W-OME-063-***
76	145	20	W-OME-076-***

ID (MM)	W.P. (PSI)	MAX LENGTH (M)	PART NO
88	145	20	W-OME-088-***
100	145	20	W-OME-100-***
125	145	20	W-OME-125-***
150	145	20	W-OME-150-***
200	145	20	W-OME-200-***

MARINE EXHAUST HARDWALL - SMOOTH COVER

Designed and approved for the delivery of cooling water and exhaust gas in boat engines pleasure craft. Ozone, heat and oil resistant cover.

ID (MM)	OD (MM)	W.P. (MPA)	MASS (KG/M)	MAX LENGTH (METRES)	PART NO
19	29	0.30	0.63	20	W-OMS-020
25	35	0.30	0.77	20	W-OMS-025
28	40	1.03	0.95	15.2	W-OMS-028
32	42	0.30	0.95	20	W-OMS-032
35	46	0.86	1.11	15.2	W-OMS-035
38	48	0.30	1.09	20	W-OMS-038
41	53	0.69	1.29	15.2	W-OMS-041
45	55	0.30	1.26	20	W-OMS-044
50	60	0.30	1.41	20	W-OMS-050
57	68	0.52	1.72	15.2	W-OMS-057
60	72	0.52	1.81	15.2	W-OMS-060
63	76	0.52	2.33	15.2	W-OMS-063
76	89	0.34	2.63	15.2	W-OMS-076
88	103	0.34	3.08	15.2	W-OMS-088
101	115	0.34	3.65	15.2	W-OMS-100
125	139	0.30	5.02	20	W-OMS-125

MARINE FILLER HOSE (Meets USCG/SAE J1527 Type A1)

Fuel Line for Marine Gasoline Tanks. Connection from the boats fuel fill port to the fuel tank. Black Chemigum tube and Black Chemivic cover, synthetic ply reinforcement



ID (MM)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
19	29.40	0.67 (100)	0.51	15.25	M-OMA-020-***
25	38.10	0.67 (100)	0.64	15.25	M-OMA-025-***
31.75	47.29	0.67 (100)	0.97	15.25	M-OMA-032-***
38	58.34	0.67 (100)	1.43	15.25	M-OMA-038-***
50.80	61.52	0.34 (50)	1.52	15.25	M-OMA-051-***
60.33	71.04	0.34 (50)	1.78	15.25	M-OMA-060-***

All dimensions are nominal.

Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



MULTI-PURPOSE RED OIL RESISTANT

Premium multipurpose hose for use in air, water, oil and many chemical applications.
Black Nitrile and red neoprene cover, synthetic ply reinforcement, Temp range -29 to +100 C
Non Conductive at 1000Volts DC.



ID (MM) (INCHES)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
5 (3/16)	11.1	1.36 (200)	0.09	228.5 (750)	M-MPR-005-***
6 (1/4)	14.0	1.36 (200)	0.15	228.5 (750)	M-MPR-006-***
8 (5/16)	15.9	2.0 (300)	0.20	213.0 (700)	M-MPR-008-***
10 (3/8)	17.5	1.36 (200)	0.26	198.0 (650)	M-MPR-010-***
12 (1/2)	22.2	1.7 (250)	0.38	137.0 (450)	M-MPR-012-***
16 (5/8)	27.0	2.0 (300)	0.45	137.0 (450)	M-MPR-016-***
20 (3/4)	29.4	1.36 (200)	0.56	106.7 (350)	M-MPR-020-***
25 (1)	36.5	1.36 (200)	0.81	76.2 (250)	M-MPR-025-***
32 (1.1/4)	44.2	1.36 (200)	1.05	122.0 (400)	M-MPR-032-***
38 (1.1/2)	50.4	1.36 (200)	1.21	122.0 (400)	M-MPR-038-***
50 (2)	65.2	1.36 (200)	1.84	61.0 (200)	M-MPR-050-***

ORTAC 250

Premium quality multipurpose hose for industrial applications. It is suitable for Air, water, petroleum oils, lubricating oils, petrol, animal fats, Alkali's, salt solutions, kerosene, paraffin, sprays and chemicals.
Non Conductive at 1000volts DC. Temp -40—+100deg C



ID (MM) (INCHES)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
5 (3/16)	12	2.1 (305)	0.10	152.4	M-ORT-005-***
6 (1/4)	13	1.7 (250)	0.12	152.4	M-ORT-006-***
8 (5/16)	15	1.7 (250)	0.21	152.4	M-ORT-008-***
10 (3/8)	17	1.7 (250)	0.24	152.4	M-ORT-010-***
12 (1/2)	21	1.7 (250)	0.30	152.4	M-ORT-012-***
16 (5/8)	24	1.7 (250)	0.38	152.4	M-ORT-016-***
20 (3/4)	29	1.7 (250)	0.51	152.4	M-ORT-020-***
25 (1)	37	1.7 (250)	0.77	152.4	M-ORT-025-***
32 (1.1/4)	45	1.7 (250)	1.07	122	M-ORT-032-***
38 (1.1/2)	53	1.7 (250)	1.40	91.4	M-ORT-038***
50 (2)	76	1.7 (250)	1.80	61	M-ORT-050***

ALSO AVAILABLE (SEE AUTOMOTIVE CATALOGUE)

RADIATOR HOSES
AIR BRAKE HOSES
VACUUM BRAKE HOSES

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



SINGLE LINE WELDING HOSE Meets AS 1335



Premium single line Acetylene(R) and Oxygen(B) Welding Hoses that meets all of the requirements of AS1335 and can be used for portable and in line gas welding service. Black SBR tube and red (acetylene) green (oxygen) Neoprene cover, synthetic ply reinforcement, temp range -40 to +82 C

ID MM	OD (MM)	W.P. MPA (PSI)	MASS (KG/M)	COIL LENGTHS METRES	PART NO
5	12.2	1.2 (175)	0.13	20 / 152	M-SL(*)-005-***
6	14	1.2 (175)	0.16	20 / 152	M-SL(*)-006-***
8	16	1.2 (175)	0.20	20 / 152	M-SL(*)-008-***
10	19	1.2 (175)	0.28	20 / 152	M-SL(*)-010-***

*Add Colour:
R—RED
B—BLUE
O—ORANGE (LPG)



TWIN LINE WELDING HOSE Meets AS 1335

Premium Welding Hose that meets all of the requirements of AS1335 and can be used for portable and in line gas welding service. Black SBR tube and red (acetylene) blue (oxygen) Neoprene cover, synthetic ply reinforcement, temp range -40 to +82 C

ID MM	OD (MM)	W.P. MPA (PSI)	MASS (KG/M)	COIL LENGTHS METRES	PART NO
5	12.2	1.2 (175)	0.26	20 / 152	M-TLW-005-***

****REF TO BRASS PRICE LIST FOR OXY / LPG FITTINGS**

TWIN WELD ASSEMBLIES WITH BRASS FITTINGS PERMANENTLY CRIMPED

Black SBR tube and red (acetylene) / blue (oxygen) Neoprene cover, synthetic ply reinforcement, temp range -40 to +82 C
Fitted with Left Hand and Right hand Female Threads

ID MM	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
5	11.1	1.0 (150)	1.19	5.0 (16)	M-TLA-005-005
5	11.1	1.0 (150)	1.69	7.5 (24)	M-TLA-005-075
5	11.1	1.0 (150)	2.18	10.0 (33)	M-TLA-005-010
5	11.1	1.0 (150)	3.29	15.0 (48)	M-TLA-005-015
5	11.1	1.0 (150)	4.25	20.0 (66)	M-TLA-005-020

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



WASHDOWN HOSE

SPECTRA HOT WASHDOWN

High quality hose for a variety of hot washdown applications.
Black Tube White cover, spiral synthetic reinforcement, temp range -29 to +100 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	23.0	2.1	0.41	152.4	M-HWG-012-***
20	30.0	2.1	0.60	152.4	M-HWG-020-***
25	38.0	1.9	0.89	152.4	M-HWG-025-***

WHITE ECW HOT WASHDOWN

Designed for floor and equipment washdown in dairies, creameries, food processing plants and paper mills.
White EPDM tube and cover, synthetic ply reinforcement, temp range -40 to +100 C



ID MM	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
12	25.0	1.75 (250)	0.53	137.0	M-HWW-012-***
20	31.8	1.75 (250)	0.72	122.0	M-HWW-020-***
25	38.0	1.75 (250)	1.02	92.0	M-HWW-025-***

PURELINE FDA GREASE PROOF WASHDOWN (smooth cover)


Designed for floor and equipment in dairies, creameries, food processing plants and paper mills.
White EPDM tube and cover, synthetic ply reinforcement, temp range -40 to +100 C



ID MM	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
12	24	1.7 (245)	0.51	20 / 152.4	M-HWP-012-***
20	30	1.7 (245)	0.60	20 / 152.4	M-HWP-020-***
25	38	1.7 (245)	0.88	20 / 152.4	M-HWP-025-***

FDA GREASE PROOF WASHDOWN (Wrapped)

Designed for floor and equipment in dairies, creameries, food processing plants and paper mills.
White EPDM tube and cover, synthetic ply reinforcement, temp range -40 to +100 C



ID MM	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES	PART NO
12	23	0.75 (116)	0.37	20	W-PWD-012-***
20	32	0.75 (116)	0.64	20	W-PWD-020-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



STEAM HOSE

STEEL STEAM—WRAPPED COVER

High Pressure, Wire reinforced hose for super heated steam and heat, fire prevention, thawing etc.
Black EPDM tube and red cover, steel ply reinforcement, temp range -40 to +232 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	25.0	1.80	0.52	20	M-SHS-012-***
20	32.0	1.80	0.76	20	M-SHS-020-***
25	38.0	1.80	0.99	20	M-SHS-025-***
32	46.0	1.80	1.31	30.5	M-SHS-032-***
38	54.0	1.80	1.63	20	M-SHS-038-***
50	67.0	1.80	2.23	20	M-SHS-050-***

FABRIC BRAIDED STEAM—WRAPPED COVER

General Purpose hose designed for use with saturated steam.
Black EPDM tube and Black cover, fabric ply reinforcement, temp range -40 to +170 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
12	24	0.8	0.41	20	W-SHF-012-***
20	32	0.8	0.57	20	W-SHF-020-***
25	35	0.8	0.54	20	W-SHF-025-***
32	46	0.8	1.05	20	W-SHF-032-***
38	53	0.8	1.20	20	W-SHF-038-***

FOOD / BEVERAGE HOSE

WHITE FLEXWING SUCTION/DELIVERY

Highly Flexible Suction & Delivery hose suitable for conveying all liquid food stuffs
White Foodgrade tube and white cover, synthetic ply reinforcement incorporating wire helix,
temp -32 to intermittent. 121 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	36.5	1.00	0.85	30.5	W-FS1-025-***
32	43	1.00	1.01	30.5	W-FS1-032-***
38	50	1.00	1.27	30.5	W-FS1-038-***
50	64	1.00	1.82	30.5	W-FS1-050-***
63	79	1.00	1.81	30.5	W-FS1-063-***
75	84	1.00	3.27	30.5	W-FS1-075-***
100	118	1.00	5.04	30.5	W-FS1-100-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



WHITE SOFTWALL DELIVERY HOSE

Tank truck or in plant service hose for discharge transfer of dry or liquid foods.

White foodgrade tube and white Nitrile cover, spiral wrapped synthetic reinforcement, temp range -35 to +82 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	36.5	0.52	0.85	30.5	W-FD1-025-***
32	42	0.52	1.01	30.5	W-FD1-032-***
38	48.5	0.52	1.20	30.5	W-FD1-038-***
50	62.5	0.52	1.37	30.5	W-FD1-050-***
75	87	0.52	1.98	30.5	W-FD1-075-***
100	114	0.52	2.75	30.5	W-FD1-100-***

VITNER CRUSH RESISTANT FOOD SUCT/DEL

Highly Flexible Suction & Delivery hose suitable for handling in plant or truck transfer of wine, beer potable water, and other liquid foodstuffs. **Incorporating a Monofilament Non Crushable Helix.**

White Foodgrade tube and grey cover, Polyester Monofilament Helix, temp range -34 to +104 C (Assembled avail)



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	41	1.7	1.04	30.5	W-FSN-025-***
38	53.5	1.7	1.45	30.5	W-FSN-038-***
50	68	1.7	2.04	30.5	W-FSN-050-***
63	81	1.7	2.62	30.5	W-FSN-063-***
76	98	1.7	3.83	30.5	W-FSN-075-***

BREWERS DELIVERY HOSE - RED

Superior Quality delivery hose suitable for conveying beer wine vinegar soft and alcoholic drinks, potable water. White Nitrile Tube and Red cover. -30degC—+70Deg C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	34	1.0	0.55	20	W-BDH-025-***
38	55	1.0	1.69	20	W-BDH-038-***
50	71	1.0	2.76	20	W-BDH-050-***
76	101	1.0	4.88	20	W-BDH-075-***

BREWERS SUCTION /DELIVERY HOSE - RED

Flexible Suction & Delivery hose suitable for conveying beer wine vinegar soft and alcoholic drinks, potable water. White FDA Nitrile tube, Red cover incorporating twin steel helix. -30deg C—+70deg C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	38	1.0	1.10	20	W-BSD-025-***
32	46	1.0	1.35	20	W-BSD-032-***
38	52	1.0	1.55	20	W-BSD-038-***
50	65	1.0	2.10	20	W-BSD-050-***
63	80	1.0	3.05	20	W-BSD-063-***
76	93	1.0	3.60	20	W-BSD-075-***
100	122	1.0	5.70	20	W-BSD-100-***

All dimensions are nominal.

Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



BLUE MILK & FOOD SUCTION

Suction & Delivery for Milk and other food stuffs. Suitable for CIP systems
White Butyl foodgrade tube and Blue SBR cover, synthetic ply reinforcement incorporating twin wires.



ID (MM)	OD (MM)	W.P. (MPA)	MASS (KG/M)	COIL LENGTHS (METRES)	PART NO
50	62	0.60	1.68	30	W-FSM-050-***
63	76	0.60	2.33	30	W-FSM-063-***
75	88	0.60	2.66	30	W-FSM-075-***

MATERIAL HANDLING HOSE

ALLCRETE FABRIC CONCRETE PLACEMENT

Premium textile Concrete Placement hose on the Australian market. Flexible with a small bend radius this hose also has excellent crush resistant properties. Black Synthetic rubber abrasion resistant tube and cover, synthetic ply reinforcement, temp range -32 to +82 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
38	59	6.9	1.58	30.5	W-CPF-038-***
50	72	6.9	2.04	30.5	W-CPF-050-***
63	86	6.9	2.59	30.5	W-CPF-063-***
75	100	5.5	3.22	30.5	W-CPF-075-***
90	113	5.1	4.01	30.5	W-CPF-090-***
100	125	4.8	4.18	30.5	W-CPF-100-***

STEEL CONCRETE PLACEMENT

Suitable for the placement of wet concrete with high head pressures this hose allows easy handling at the critical flex areas of a concrete boom truck Crush resistant and full suction capabilities
Black Synthetic rubber abrasion resistant tube and cover, steel ply reinforcement, temp range -40 to +82C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
75	101	6.9	5.13	15.25	W-CPS-075-***
100	127	5.5	6.62	15.25	W-CPS-100-***
125	152	4.8	8.07	15.25	W-CPS-125-***

SAND & SHOT BLAST

Light Duty Sand Blast Hose for use in sand and grit blasting service.
Black synthetic rubber abrasion resistant tube and cover, synthetic ply reinforcement, temp range -32 to +82 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
20	38	1.00	1.01	30.5	W-SBH-020-***
25	48	1.00	1.56	30.5	W-SBH-025-***
32	55	1.00	1.88	30.5	W-SBH-032-***
38	60	1.00	2.18	30.5	W-SBH-038-***
50	73	1.00	2.53	30.5	W-SBH-050-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



ARTRAC



Used for material handling applications including drain cleaning, sand, gravel, cement, fly ash, glass, metals and slurries Thermoplastic blend of Polyurethane and PVC (Static conductive) tube,
Thermoplastic alloyed blend of Nitrile, polyurethane and PVC (non conductive) cover Black Rigid PVC Helix, temp range -35 to +70 C

ID (MM)	OD (MM)	VAC (IN/HG)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
32	41	29	0.51	30.5	W-ART-032
38	48	29	0.60	30.5	W-ART-038
50	62	29	1.00	30.5	W-ART-050
63	77	29	1.29	30.5	W-ART-063
76	93	29	1.73	30.5	W-ART-075
90	102	29	1.84	30.5	W-SPR-090-***HD
102	122	29	3.21	30.5	W-ART-100
127	147	29	3.87	15.2	W-ART-125
152	179	29	5.10	15.2	W-ART-150
203	234	29	8.69	6.0	W-ART-200
252	284	29	11.85	6.0	W-ART-250

MUFF COUPLING



Dry material Suction and Delivery hose. Suitable for transfer of dry cement, sand, gravel, feed and seeds.
Black SBR abrasion resistant tube and cover, synthetic ply reinforcement with Steel Helix, temp range -35 to +70 C

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
75	107.0	0.70	6.06	20	W-MCH-075-***
100	132.0	0.70	7.45	20	W-MCH-100-***
150	182.0	0.70	11.94	20	W-MCH-150-***
200	237.0	0.70	18.17	12.0	W-MCH-200-***
250	288.0	0.70	24.63	10.0	W-MCH-250-***

AUSMAFLEX AIRSEEDER / DUST COLLECTOR



A light duty, flexible, hard wearing dust extraction hose, grain seed transfer.
Green Gum abrasion resistant tube (3mm thick) and black SBR cover, synthetic ply reinforcement with Steel Helix.

ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
75	92.0	1.12	2.90	18.3	W-AUS-075-***
100	118.0	0.85	3.80	18.3	W-AUS-100-***
125	143.0	0.69	4.70	18.3	W-AUS-125-***
140	156.0	0.63	5.20	18.3	W-AUS-140-***
150	168.0	0.58	5.60	18.3	W-AUS-150-***
200	219.0	0.44	7.40	12.0	W-AUS-200-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE

PRICING IN INDUSTRIAL PRODUCTS PRICE LIST


**FLUID HANDLING
SOLUTIONS**

DRY MATERIAL PNEUMATIC TRANSFER

Bulk Handling Hose for the discharge of dry bulk cement, sand, gravel and other abrasive material Black synthetic rubber abrasion resistant static conductive tube and black cover, synthetic ply reinforcement, temp range -32 to +82 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
100	113.0	0.34	2.14	20/30.5	W-MHP-100-***

HOT TAR WAND HOSE

High quality wand hose used for asphalt crack filling applicator and dispensing service. Black heat resistant tube and cover, Spiral plied with 2 wire helix, temp range -32 to +204 C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
19	35	2.1	1.01	30.5	W-HTW-020-***
25	41	2.1	1.25	30.5	W-HTW-025-***

CABLE TRAILING FRAS

Fabric reinforced hose hose for use as an electrical cable cover in underground coal mines. This hose complies with the combustion and electrical properties of AS2660.



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
13	23	N/A	0.43	40	W-FCT-012-***
16	27	N/A	0.49	40	W-FCT-016-***
20	39	N/A	0.56	40	W-FCT-020-***
25	35	N/A	0.70	40	W-FCT-025-***
29	38	N/A	0.85	40	W-FCT-029-***
32	41	N/A	1.00	40	W-FCT-032-***
38	48	N/A	1.16	40	W-FCT-038-***
44	55	N/A	1.28	40	W-FCT-044-***
50	60	N/A	1.57	40	W-FCT-050-***

FRAS ANTI STATIC SUCTION

Heavy Duty water suction and delivery hose for full suction and high discharge pressures. Handles sewerage water and mud. Black SBR Tube and Chloroprene cover (Steel helix) Complies with FRAS Standards. -40degC—+100deg C



ID (MM)	OD (MM)	W.P. (MPA)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
51	63	1.0	1.79	20 60	W-FAS-050-***
76	87	1.0	3.00	20	W-FAS-076-***
102	116	1.0	4.17	20	W-FAS-100-***
152	170	1.0	10.22	20	W-FAS-150-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



ACID / CHEMICAL HOSE

BLUE THUNDER 7373T UHMWPE



Corrugated Hose providing flexibility and durability. The Ultra High Molecular Weight Polyethylene (UHMWPE) will handle 98% of the most common chemicals without leaching and contaminating the product being conveyed.

ID (MM)	OD (MM)	W.P. (PSI)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	37	200	0.91	30.5	W-UHM-025-***
32	43	200	0.97	30.5	W-UHM-032-***
38	50	200	1.24	30.5	W-UHM-038-***
51	66	200	2.08	30.5	W-UHM-050-***
76	93	200	3.26	30.5	W-UHM-075-***
102	119	150	4.62	30.5	W-UHM-100-***

BLUE FLEXWING XLPE



Smooth Blue cover with XLPE tube, double wire helix. Handles the majority of today's industrial chemicals in pressure, gravity or suction service. Temp -32deg C—+66deg C

ID (MM)	OD (MM)	W.P. (PSI)	WEIGHT (KG/M)	COIL LENGTHS (METRES)	PART NO
25	37	200	0.82	30.5	W-BFW-025-***
32	44	200	1.04	30.5	W-BFW-032-***
38	52	200	1.41	30.5 122	W-BFW-038-***
50	65	200	1.82	30.5 122	W-BFW-050-***
63	79	200	2.46	30.5 122	W-BFW-063-***
75	94	200	3.33	30.5	W-BFW-075-***
102	120	200	4.49	30.5	W-BFW-100-***

CUTS OF FLEXWING MAY NOT ALWAYS BE AVAILABLE, PLEASE PHONE

PAINT FLUID HOSE



Nylon tube ensures this hose is suitable for both water and oil based paints. Transparent Nylon tube and black rubber cover, synthetic ply reinforcement, temp range -18 to +88 C

ID MM (INCHES)	OD (MM)	W.P. MPA (PSI)	WEIGHT (KG/M)	COIL LENGTHS METRES (FEET)	PART NO
6	13	5.2 (750)	0.12	152.0 (500)	M-PSH-006-***
10	17	5.2 (750)	0.22	152.0 (500)	M-PSH-010-***
12	22	5.2 (750)	0.33	152.0 (500)	M-PSH-012-***

All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST



Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE



All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





All dimensions are nominal. Products may vary slightly to those pictured

PRICING FOR THIS SECTION FOUND IN THE INDUSTRIAL PRODUCTS PRICE LIST

Customer Service - Phone: 1300 349 320 Fax: 1300 349 321

www.fhshose.com.au

MELBOURNE - SYDNEY - NEWCASTLE





FLUID HANDLING SOLUTIONS

Abrasives
Airbrake Fittings
Airline Couplings
Automotive Belts
Ball Valves
Bauer Fittings
Band-It
Brass Fittings
Camlock Fittings
Chain & Sprockets
Check Valves
Claw Couplers
Composite Hose
Couplings
Ducting
Filter Regulators
Fire Fittings
Gate Valves
Glue
Hose Assemblies
Hose Fittings
Hose Reels
Hydraulic Adaptors
Hydraulic Couplings
Hydraulic Hose
Industrial Belts
Layflat Hose
Nozzles
Nylon Tube
Pipe Fittings
Pneumatics
Poly Fittings
Polyurethane Tube
Pool Hose
Pressure Gauges
PTFE Fittings
Push-In Fittings
PVC Hose
Quick Couplings
Rubber Hose
Sheet Rubber
Silicone Hose
Stainless Steel Fittings
Stainless Steel Hose
Strainers
Steam Fittings
Super Clamps
Tank Fittings
Tubing
Wormdrives

LOCATIONS



BRAESIDE
Unit 5 / 200-208
Boundary Rd
Braeside VIC. 3195

BAYSWATER
Unit 1 / 477
Dorset Rd
Bayswater VIC. 3153

CUSTOMER SERVICE

P: 1300 349 320

F: 1300 349 321



SYDNEY
25 Clyde St
Rydalmere NSW. 2116

NEWCASTLE
Unit 2 / 34
Portside Crescent
Maryville NSW. 2293

www.fhshose.com.au